


# Brief Introduction



Model: RK8120  
Omnidirectional Barcode Scanner

- **High performance:** high precision, high reading speed, high compatibility, etc. Widely used in retail, supermarkets, tobacco, logistics, warehousing, medical care, clothing and other fields; highly cost-effective products.
- **Compatible Models:** LS9203、LS9208、MS7120、Z6170、Z6030、Z6070、CBF7020、MX6000、MX6030、MX7020、CO5300、CO5330、XL7721、XL7720, etc.
- **Super Compatibility:** Compatible with major operating systems: Win2003 / WinXP / Vista / Win7 / Win8, Apple MAC; Android, IOS.

# Product Features



- Powerful 32-bit quad-core CPU: high operation speed, strong decoding capability
- High Reading Speed: 1500 scans/sec.
- Long Reading Distance: 0--30cm
- High Precision:  $\geq 5\text{mil}$ .
- 360-degree omni-directional scanning: 20-line, 5 directions, each direction 4 parallel lines
- High integration: new generation of programming techniques, direct CPU hardware decoding, reducing failure rate.
- USB Driver Free: Plug and Play
- Inverse Autodetect

# Product Features

Light  
Instruction



Pulley  
design, the  
head  
scanning  
angle can be  
adjusted as  
needed

Easy installing  
and removing  
interface

- **Military Grade Quality Assurance:** each part is rigorous tested; ensure 100 percent qualified.
- **Ageing Test:** Each product has been tested under room temperature and high-temperature; and through the practical operation test.
- **BERT:** the product has passed test of 30 million times without error.
- **Silent Motor:** Taiwan precision motors, balancing test, to ensure that achieve the industry's most silent products.

# Technical Parameters

<b>Size</b>	154*105*111mm (H/W/L)
<b>Weight/Color</b>	317g/Black/White
<b>Voltage</b>	5.0VD± 10%
<b>Current</b>	230mA
<b>Power Consumption</b>	1W
<b>Light Source</b>	650 Nano visible laser
<b>Scan Mode</b>	Omnidirectional 20-line, 5 directions, each direction 4 parallel lines
<b>Reading Speed</b>	1500 scans/sec.
<b>Depth of Scan</b>	0-25.00CM@13mil(100% UPC/EAN)
<b>Rated Operating Range</b>	5mil:(38%)1.0~5.0cm
	7.8mil:(60%)0~18.0cm
	10.4mil:(80%)0~22.0cm
	13mil(130%)0~25.0cm
<b>Precision</b>	5mil
<b>Interface</b>	USB

<b>Symbologies</b>	UPC/EAN/UCC 128/Code128/Code 39/Code 93 Trioptic/Interleavec 2 of 5/Industridl 2 of 5/Matrix 2 of 5/Code 11/Codabar/MSI,etc.
<b>Operating Temperature</b>	0°C~40°C
<b>Storage Temperature</b>	-40°C~70°C
<b>Humidity</b>	5%~95%(Non-condensing)
<b>Light resistance</b>	It can be used in normal indoor lighting and outdoor natural light conditions, fluorescent, incandescent, mercury vapor lights and sodium vapor lights: 450Ft Candles(4,844 Lux), sunlight: 8000Ft Candles(86,111 Lux)
<b>Laser Security</b>	CDRH IIa class laser product
	IEC 60825 1 class laser product

# Appearance & Packaging



- **Delicate Packaging:** by using imported cardboard, the box can bear an external force of 50kgs. Compact box size saves a lot of freight cost.
- **20pcs/Carton**
- **Product Size:** 154\*105\*111mm
- **Single Box Size:** 192\*128\*111mm
- **Carton Size(20pcs/Carton):** 685\*414\*247mm

# Product Shot

